

LED SUSPENSION LIGHT

horozelectric.com.ua +38 (096) 8312125




Product&Family Code:

019 012 0035

DELUXE-35

Technical Data	
Voltage (V)	220-240
Product Wattage (W)	35
Equivalence with incandescent lamp(W)	280
Colour Render Index (Ra)	>Ra80
Colour Temperature (K)	4000K
Materials	Aluminium + Iron + Acrylic
Protection Class	I
Dimmable	No
EEI	A to A ⁺⁺
Warm-up time up to 60 %of the full light output	Instant Full Light
Luminous Flux (lm)	2000
Luminous Efficacy (Im/W)	57
Rated Life (hrs) (L)	50.000
IP Rating	20
Power Factor	>0.9
Beam Angle	120°


Technical Drawing



Applications

• LED Suspension Light has been specifically designed for use indoors and is ideal for both hospitality and residential lighting.

Photometric Diagram



6 C9 Plane beam angle(50%) C90 Plane beam angle(50%) C90 Plane beam angle(50%):137.3(DEG) C90 Plane beam angle(50%):138.8(DEG)

Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- SMD LED Lamp Base
- Very low energy consumption

















