
LED SUSPENSION LIGHT

horozelectric.com.ua +38 (096) 8312125




WHITE

Technical Drawing



Photometric Diagram



C0 Plane beam angle(50%):105.3(DEG) C90 Plane beam angle(50%):105.5(DEG)


Product&Family Code: 019 001 0024



| Technical Data | |
|-------------------------------|-----------------------------|
| Voltage (V) | 220-240 |
| Product Wattage (W) | 24 |
| Equivalence with incandescent | 192 |
| lamp(W) | |
| Colour Render Index (Ra) | >Ra70 |
| Colour Temperature (K) | 4000K |
| Materials | Metal + Aluminium + Acrylic |
| Protection Class | I |
| Dimmable | No |
| EEI | A to A ⁺⁺ |
| Warm-up time up to 60 %of | Instant Full Light |
| the full light output | |
| Luminous Flux (lm) | 1680 |
| Luminous Efficacy (Im/W) | 70 |
| Rated Life (hrs) | 50.000 |
| IP Rating | 10 |
| Power Factor | >0.9 |
| Beam Angle | 120° |

Applications

• LED Suspension Light has been specifically designed for use indoors and is ideal for both hospitality and residential lighting.



Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- SMD LED Lamp Base
- Very low energy consumption















